


The NOVA logo is positioned in the top right corner of the image. It consists of the word "NOVA" in a bold, black, sans-serif font. The letter "V" is stylized with a red and blue geometric shape integrated into its structure. The logo is set against a white rectangular background that is placed over a colorful, multi-colored diamond-patterned graphic on the right side of the overall image.The word "PARTITIONS" is centered horizontally across the middle of the image. It is written in a large, bold, white, sans-serif font. The text is overlaid on a semi-transparent dark grey horizontal band that spans the width of the image. The background behind the text is a photograph of a modern office interior with glass-walled cubicles and desks.

Headquarter Al-Mwager Industrial Zone  +962 6 402 6251  +962 6 402 6252 | P.O.Box: 143770 Amman 11814
 +962 79 802 2022  info@nova.com.jo www.nova.com.jo



Technical Information

PARTITION SYSTEM W101

Structural elements

Partition walls made of panels of melamine finish chipboard wood spaced both Vertically and Horizontal of 6mm, total thickness of the partitions is 100mm. Structure composed of galvanized steel uprights spaced 10/10mm outer section 34 X 64mm slotted over the whole height with 32mm pitch, on which are hooked onto the panel, the glazed panels, and the structural parts horizontal cross. Along the uprights there are openings from approx. 50 X 50mm used for passage of electric cables, a coextruded PVC gasket, installed between the uprights and the panels, complete sealing. Uprights are also provided with vertical leveling precision adjustment consists of pin diameter 12mm driven by a common hex wrench, the adjustment is +/- 25mm. Between floor ceilings, side walls and the partition guides are installed in. Guides are made of sheet coated with PVC self-extinguishing by 60 X 55 X 0.8mm and / or aluminum rails depending on the type of wall, arranged for the passage of cables, a self-adhesive gasket completes the seal to the ground. The Cross are made of 10/12 mm galvanized steel with n. 2 slots for the passage of electric cables, a self-adhesive PVC gasket is interposed between the upright and the upper channel.

Finishes

Panels made of melamine finish chipboard. 18mm, banded on 4 edges with PVC.

On the back of the panels there are holes to accommodate the galvanized steel hooks to fix the panels on uprights. Vertical filling panels are finished with a PVC profile previously installed along the Wall that covers the side cut of the panel.

Starting from a steel structure the demountable partition NOVA W101 offers countless configurations, finishes and colors. An inner cavity allows the passage of electric cables and data, in addition to the insertion of insulating material to increase the capabilities of sound-absorbency.

Nova the system of demountable
Partition, storage walls and components for office furnishing.

The mission is to establish an indissoluble link between customer, designer and the company to search for perfection in every single step of the project.

A well organized and efficient network of sellers use our experience to realize worldwide projects.







Steel, wood, aluminum and glass are mixed together in this product that offers endless design options.

High acoustic performance, strength and attention to detail are the features that make this demountable partition a reference.

















